



PVC FINISH STEEL RAISED FLOOR

Panel structure Full steel, independent four corners support structure. Lower plane is ST14 stretched plate, surface plane is SPCC hard steel painted with conductive antistatic epoxy resin. Foaming cement in filled. Lock hole in four corners.

Advantage High dimensional precision, strong load ability And shock proof. Adjustable height for pedestal, assembly agility, large wire, good exchange ability. High recycled.



TYPE		FS800
Panel Size		600*600*35mm
Concentrated Load	N	3550
	KG	363
Impact load		536
Ultimate Load /N		11250
Uniform Load N/M ²		16100
Rolling Load /N	10times	3560
	10000times	2670
Reaction to Fire		A1
Weight per Panel(KG)		16
Pedestal and Stringer		Flat pedestal: Top size:76*76*3mm, Bottom:95*95*2mm,FFH=15cm,Other size can be customized,Galvanized for anti-rust Stringer:570*32*21mm, Thickness=1.0mm,Galvanized gold color or white color.



MATCH IN ONE SQM :

- PANEL 2.78PCS
- PEDESTAL 3.3PCS
- SCREW 11.2PCS
- STRINGER 5.2PCS



Application:5A class office building and occasions which require overhead and large wires. Paving carpet, PVC etc for elegant appearance ,

