



## HPL FINISH STEEL RAISED FLOOR

**Panel structure** Full steel, independent four corners support structure. Lower plane is ST14 stretched plate, surface plane is SPCC hard steel painted with conductive antistatic epoxy resin. Foaming cement infilled. Lock hole in four corners.

**Advantage** High dimensional precision, strong load ability And shockproof. Adjustable height for pedestal, assembly agility, large wire, good exchangeability. High recycled.



TYPE		FS800
Panel Size		600*600*35mm
Concentrated Load	N	3350
	KG	363
Impact load /N		536
Ultimate Load /N		11250
Uniform Load N/M <sup>2</sup>		16100
Rolling Load /lb	10times	3560
	10000times	2670
Reaction to Fire		A1
Weight per Panel(KG)		13
Pedestal and Stringer		Flat pedestal: Top size:76*76*3mm, Bottom:95*95*2mm,FFH=15cm,Oth er size can be customized, Galvanized for anti-rust Stringer:570*32*21mm, Thickness=1.0mm,Galvanized gold color or white color.



### MATCH IN ONE SQM:

- PANEL 2.78PCS
- PEDESTAL 3.3PCS
- SCREW 11.2PCS
- STRINGER 5.2PCS

**Application:**5A Class office building and occasions which require overhead And large wires. Paving carpet, PVC etc for elegant appear-ance, Also this raised flooring is applicable for Server Room, Data Room and Information Technology Room.

